



- Robust steel profile construction.
- Sturdy and compact enough to fit through standard door and to operate in congested areas.
- Lifting function operated by foot and hand controls.
- Allows the operator to work without having to perform extreme body movements.



C-Profile
PREMIUM



C-Section



I-Section

On Demand Custom Specifications are Available

TECHNICAL SPECIFICATIONS

MODEL		RB-105		
Rated lifting capacity	(kg)	1T/1.5T/2T	1T/1.5T/2T	1T/1.5T/2T
Max Lifting Height (H1)	(mm)	1600	2500	3000
Lowered height of forks	(mm)	85-110	85-110	110
Fork length (L1)	(mm)	900-1000	900-1000	1000
Adjustable width of forks	(mm)	210-590	210-590	580-590
Lifting speed	(mm/s)	10 or 20	10	10
Lowering speed	(mm/s)	Controllable	Controllable	Controllable
Outer width of front legs	(mm)	750-760	750-760	760
Operation power of hand crank	(kg)	24-40	24-40	40
Min. refuel volume for fuel tank	(L)	1.6-3	1.6-3	3
Front wheel size	(mm)	85x50-100x50	85x50-100x50	100x50
Rear wheel size	(mm)	180x50	180x50	180x50
Overall Length (L)	(mm)	1360	1410	1410-1580
Overall Width (W)	(mm)	755	780	780-800
Overall Height (H)	(mm)	2040	1540-2040	1540-2070
Self weight	(kg)	140-295	140-295	150-295

