



Electric Wire Rope Hoist

- Model RB-122 Single Speed Hoist With Trolley
- Model RB-122 Double Speed Hoist With Trolley

With a compact, light weight, small size and easy to use, and other characteristics, it can be installed on a separate overhead I-beam, can also be installed in matching electric single-girder, double beam cantilever, such as gantry cranes for use. Fine occasions in the operation, when the CD1- electric hoist the hoisting speed can not meet the requirements, should be selected from MD1-or two-speed electric hoist.

****On Demand Custom Specifications are Available****

TECHNICAL SPECIFICATIONS



RB-122

RB-122								
Capacity	0.5T	1T	1.5T	2T	3T	5T	7.5T	10T
STD. Lift (M)	6	6	6	6	6	6	6	6
Hoisting	Speed MPM	3.5/4	3.5/4	3.5/4	3.5/4	4.	4.	3
	Motor MPM	0.75	2.	2	3	5	6	10
Cross Travel	Speed MPM	15/17	17/20	17/20	15/17	15	15	15
	Motor Hp	0.25	0.25	0.25	0.50	0.50	0.75	1
No. of Fall	2	2	2	2	2	4	4	4
Head Room (HD)	635	635	635	720	920	920	1350	1600
Total Length (L)	680	680	680	845	1015	1015	1090	1220
Total Width (W)	570	570	570	620	870	870	870	1100
Total Height (H)	780	790	800	875	1170	1170	1600	1850
A	440	440	440	560	675	675	700	770
B	100	100	100	145	190	190	220	250
C	140	140	140	140	150	150	170	200
D	440	440	440	525	700	700	700	850
E	425	425	425	420	420	455	455	500
F	200	200	200	230	260	260	260	300
Weight (KGS.)	185	190	200	280	365	560	700	1060