

RB-127 & RB-135

Mobile Ramps RB-127 & RB-135

Hydraulic Mobile Ramp

Mechanical Mobile Ramp

Key Features:

MANUAL OPERATION:

Relies on mechanical means for raising and lowering the ramp, making it suitable for areas without access to power sources.

• DURABILITY:

Constructed from robust materials to withstand heavy loads and frequent use.

• VERSATILITY:

Compatible with various types of trucks and loading docks.

SAFETY:

Designed with safety features to prevent accidents and ensure the safety of operators and goods.

• COST-EFFECTIVE:

Typically lower initial cost compared to hydraulic ramps, but may require more manual effort to operate.

TECHNICAL SPECIFICATIONS

Model	Capacity	Platform size (mm)									
	(kg)	Α	В	C	D	E	F	G	Н	J	1.0
	6000	6000	3000	1000	300	10300	1800	2100	1200	1600	400
	8000	6000	3000	1000	300	10300	1800	2100	1200	1600	400
RB-127	10000	7000	3000	1000	300	11300	1800	2100	1200	1600	400
	12000	7000	3000	1000	300	11300	1800	2100	1200	1600	400
	15000	7000	3000	1000	300	11300	1800	2100	1200	1600	400



Key Features:

• ADJUSTABLE HEIGHT:

Allows the ramp to be adjusted to match the height of various loading docks or trucks.

• SMOOTH OPERATION:

Hydraulic system provides smooth and controlled raising and lowering of the ramp.

• VERSATILITY:

Can be used with a variety of trucks, trailers, and loading docks.

• DURABILITY:

Built to withstand heavy-duty usage and harsh industrial environments.

• EFFICIENCY:

Increases efficiency by providing a bridge between the dock and the truck for seamless loading and unloading operations.

TECHNICAL SPECIFICATIONS

Capacity	Platform size (mm)									
(kg)	Α	В	C	D	E	F	G	Н	J	- 1
6000	6000	3000	1000	300	10300	1800	2100	1100	1600	500
8000	6000	3000	1000	300	10300	1800	2100	1100	1600	500
10000	7000	3000	1000	300	11300	1800	2100	1100	1600	500
12000	7000	3000	1000	300	11300	1800	2100	1100	1600	500
15000	7000	3000	1000	300	11300	1800	2100	1100	1600	500
	(kg) 6000 8000 10000 12000	(kg) A 6000 6000 8000 6000 10000 7000 12000 7000	(kg) A B 6000 6000 3000 8000 6000 3000 10000 7000 3000 12000 7000 3000	(kg) A B C 6000 6000 3000 1000 8000 6000 3000 1000 10000 7000 3000 1000 12000 7000 3000 1000	(kg) A B C D 6000 6000 3000 1000 300 8000 6000 3000 1000 300 10000 7000 3000 1000 300 12000 7000 3000 1000 300	(kg) A B C D E 6000 6000 3000 1000 300 10300 8000 6000 3000 1000 300 10300 10000 7000 3000 1000 300 11300 12000 7000 3000 1000 300 11300	(kg) A B C D E F 6000 6000 3000 1000 300 10300 1800 8000 6000 3000 1000 300 10300 1800 10000 7000 3000 1000 300 11300 1800 12000 7000 3000 1000 300 11300 1800	(kg) A B C D E F G 6000 6000 3000 1000 300 10300 1800 2100 8000 6000 3000 1000 300 10300 1800 2100 10000 7000 3000 1000 300 11300 1800 2100 12000 7000 3000 1000 300 11300 1800 2100	(kg) A B C D E F G H 6000 6000 3000 1000 300 10300 1800 2100 1100 8000 6000 3000 1000 300 10300 1800 2100 1100 10000 7000 3000 1000 300 11300 1800 2100 1100 12000 7000 3000 1000 300 11300 1800 2100 1100	(kg) A B C D E F G H J 6000 6000 3000 1000 300 10300 1800 2100 1100 1600 8000 6000 3000 1000 300 10300 1800 2100 1100 1600 10000 7000 3000 1000 300 11300 1800 2100 1100 1600 12000 7000 3000 1000 300 11300 1800 2100 1100 1600





0